

TSG Smart 4G Camera WS-SNC267G-20X

1. Product Pictures



2. Features

2.0 megapixel HD 4G IP camera, maximum resolution 1920*1080;

Support 4G, support AP mode;

Support up to 512G TF card storage;

4.7-94mm 20X optical zoom auto focus lens;

Built-in MIC, support voice monitor;

Pan tilt rotation, horizontal: 355° & vertical:90°;

Human Shape detect, draw line, box, ploy box Alarm;

Support different country 4G band, just change 4G modem;

Waterproof level IP66;



6pcs array infrared LEDs, night vision distance 80m;

Support P2P, view & anywhere & anytime;

Elegant outline and easy installation;

Provide android & ios APP and professional CMS PC client software; OEM, ODM

are available.

3. Specifications

Model	WS-SNC267G-20X	
Video	Sensor	2.0 megapixel 1/2.8" SONY307 star light CMOS
	Video resolution	Main stream: 1920x1080@30fps, 1280x720@30fps, 960x540 etc. Sub stream: 640x480@30fps, 640x320@30fps, 480x320 etc.
	Video compression	H.264
	Lens	4.7-94mm 20X optical zoom auto focus lens
	View angle	61.4°~3.6°
	Night vision	6pcs array infrared LEDs, night vision distance 80m
Audio	Audio compression	AAC/G.711
	Audio code rate	8Kbps, 16bit
	Audio input	Built-in MIC, support voice monitor
	Audio output	Support, can connect speakers
Audio	Audio compression	AAC/G.711
	Audio code rate	Rate adaptive
	Audio input	Support, can connect the pickup and MIC
	Audio output	Support, can connect speakers
Alarm	Motion detecting alarm	Can set sensitivity and area can be set
	AI alarm	Human shape detect, draw box\line, ploy box alarm
	Alarm linkage	Alarm send pictures to cloud server, Alarm upload pictures and videos to the FTP server, Alarm record pictures and videos to Micro SD card,



		Alarm mobile phone message push
	Alarm recording	Support Micro SD card and PC client linkage alarm recording
4G	4G standard	FDD-LTE/TDD-LTE
	4G frequency range(support change other band module)	B1(2100MHz), B3(1800MHz), B7(2600MHz), B8(900MHz), B20(800MHz), B38(2600MHz), B40(2300MHz), B41(2500MHz)
	Interface type	Micro SIM card, Plug and play, no need to set
Network	2.4G WiFi	AP mode or Station mode
	LAN	10/100Mbps Ethernet
Storage	Micro SD card	Support up to 512G micro SD card
	Recording mode	Alarm record, timing record,
	Video playback	Support APP, IE browser, remote client play and download the video
PTZ	Rotation angle	Horizon: 0° ~ 355°, Vertical: 0° ~ 90°
	Horizontal speed	20°~ 40°/S
	Vertical speed	10°~ 20°/S
	Preset	Support 8 preset points
General specification	Power	DC12V 2A
	Operating environment	Environment -20°C~+60°C(-4°F~+140°F), Humidity 10% ~ 90%, non-condensing
	Waterproof level	IP66
	Product size	190mm×130mm×235mm(L×W×H)
	Product weight	1.4kg
	Package size	275mmx230mmx170mm(L×W×H)
	Package weight	1.8kg
Reset button	Support	